

Single Row Inch Size(old)

Mga sukat (mm)			Basic Load Ratings(KN)		Fatigue load limit (Pu)(KN)	Rated speed		Weight (KG)	Hindi.	Series	Mga sukat (mm)					Shoulder and Chamfer Dimensions(mm)										Calculation Factor										
d	D	T	Dynamic(Cr)	Static(Cor)		Reference Rotating Speed	Limit Rotating Speed				d	d1	B	C	r1,2	r3,4	a	da	db	Da(mini)	Da(max)	Db	Ca	Cb	ra	rb	e	Y	Y0							
34,988	59,974	15,875	38	44	4.5	9000	12000	0.17	*L68149/111/Q	L68100	34,988	48.4	16,764	11,938	3.5	1.3	13	41	46	52	53.5	56	3	3.5	3	1.3	0.43	1.4	0.8							
1,3775	2,3280	0,6250	38	44	4.5	9000	12000	0.17	*L68149/110/Q	L68100	1,3775	48.4	0,6600	0,4700	0.14	0.05	13	41	46	52	53.5	56	3	3.5	3	1.3	0.43	1.4	0.8							
34,988	59,131	15,875	38	44	4.5	9000	12000	0.17	*L68149/110/Q	L68100	34,988	48.4	16,764	11,938	3.5	1.3	13	41	46	52	53.5	56	3	3.5	3	1.3	0.43	1.4	0.8							
1,3750	3,0000	1,1563	90	106	11.8	7000	9500	0.66	*HM89446/2/410/2/QCL7C	HM89400	1,3750	59.3	1,1250	0,9063	0.14	0.13	23	44	46	58	65	72	3	6	3	3	0.54	1.1	0.6							
34,925	76,200	29,370	90	106	11.8	7000	9500	0.66	*HM89446/2/410/2/QCL7C	HM89400	34,925	59.3	28,575	23,020	3.5	3.3	23	44	46	58	65	72	3	6	3	3	0.54	1.1	0.6							
1,3750	3,0000	1,1563	85.8	106	12	6700	10000	0.63	31594/31520/Q	31500	1,3750	55.6	1,1250	0,9375	0.06	0.13	20	44	42	62	64.5	71	4	5.5	1.5	3	0.4	1.5	0.8							
34,925	76,200	29,370	85.8	106	12	6700	10000	0.63	31594/31520/Q	31500	34,925	55.6	28,575	23,812	1.5	3.3	20	44	42	62	64.5	71	4	5.5	1.5	3	0.4	1.5	0.8							
1,3750	2,8750	1,0625	88	93	10.4	8000	10000	0.52	*23690/23620/QCL7C	23600	1,3750	52.3	1,0625	0,8750	0.14	0.6	19	42	46	59	65	67	3	4.5	3	1.5	0.37	1.6	0.9							
34,925	73,025	26,988	88	93	10.4	8000	10000	0.52	*23690/23620/QCL7C	23600	34,925	52.3	26,975	22,225	3.5	1.5	19	42	46	59	65	67	3	4.5	3	1.5	0.37	1.6	0.9							
1,3750	2,8750	0,9375	72.1	88	9.8	7000	10000	0.47	25877/2/25821/2/Q	25800	1,3750	52.5	0,9688	0,7500	0.06	0.03	15	44	42	62	66.5	67	5	4.5	1.5	0.8	0.3	2	1.1							
1,3750	2,8438	1,0000	78	90	10	7500	10000	0.50	*HM88649/2/610/2/QCL7C	HM88600	1,3750	55.9	1,0000	0,7812	0.09	0.09	20	42	44	57	63	68	5	5.5	2	2	0.54	1.1	0.6							
34,925	73,025	23,812	72.1	88	9.8	7000	10000	0.47	25877/2/25821/2/Q	25800	34,925	52.5	24,608	19,050	1.5	0.8	15	44	42	62	66.5	67	5	4.5	1.5	0.8	0.3	2	1.1							
34,925	72,233	25,400	78	90	10	7500	10000	0.50	*HM88649/2/610/2/QCL7C	HM88600	34,925	55.9	25,400	19,842	2.3	2.3	20	42	44	57	63	68	5	5.5	2	2	0.54	1.1	0.6							
1,3750	2,7170	0,7813	53.9	67	7.35	7500	11000	0.34	14137A/14276/Q	14000	1,3750	50.7	0,7710	0,6250	0.06	0.05	15	43	42	47	61.5	63	3	3.5	1.5	1.3	0.37	1.6	0.9							
34,925	69,012	19,845	53.9	67	7.35	7500	11000	0.34	14137A/14276/Q	14000	34,925	50.7	19,583	15,875	1.5	1.3	15	43	42	47	61.5	63	3	3.5	1.5	1.3	0.37	1.6	0.9							
1,3750	2,5625	0,7100	54	57	6.2	8500	11000	0.25	*LM48548A/510/Q	LM48500	1,3750	50	0,7200	0,5500	0.03	0.05	14	42	40	57	58.5	61	3	4	0.8	1.3	0.37	1.6	0.9							
1,3750	2,5625	0,7100	54	57	6.2	8500	11000	0.25	*LM48548/510/Q	LM48500	1,3750	50	0,7200	0,5500	0.14	0.05	14	42	46	57	58.5	61	3	4	3	1.3	0.37	1.6	0.9							
34,925	65,088	18,034	54	57	6.2	8500	11000	0.25	*LM48548A/510/Q	LM48500	34,925	50	18,288	13,970	0.8	1.3	14	42	40	57	58.5	61	3	4	0.8	1.3	0.37	1.6	0.9							
34,925	65,088	18,034	54	57	6.2	8500	11000	0.25	*LM48548/510/Q	LM48500	34,925	50	18,288	13,970	3.5	1.3	14	42	46	57	58.5	61	3	4	3	1.3	0.37	1.6	0.9							
1,3125	2,7170	0,7813	53.9	67	7.35	7500	11000	0.35	14131/14276/Q	14000	1,3125	50.7	0,7710	0,6250	0.03	0.05	15	43	38.5	47	61.5	63	3	3.5	0.8	1.3	0.37	1.6	0.9							
33,338	69,012	19,845	53.9	67	7.35	7500	11000	0.35	14131/14276/Q	14000	33,338	50.7	19,583	15,875	0.8	1.3	15	43	38.5	47	61.5	63	3	3.5	0.8	1.3	0.37	1.6	0.9							
1,3125	2,6875	0,8750	63	69.5	7.8	8000	11000	0.38	*M88048/2/010/2/QCL7C	M88000	1,3125	52.3	0,8750	0,6875	0.03	0.06	19	41	38.5	54	60.5	64	3	4.5	0.8	1.5	0.54	1.1	0.6							
1,2500	2,8750	1,1563	81.5	95	10.4	7500	10000	0.62	*HM88542/2/510/2/QCL7C	HM88500	1,2500	56.9	1,0938	0,9063	0.05	0.13	23	42	38	55	62	69	3	6	1.3	3	0.54	1.1	0.6							
33,338	68,262	22,225	63	69.5	7.8	8000	11000	0.38	*M88048/2/010/2/QCL7C	M88000	33,338	52.3	22,225	17,462	0.8	1.5	19	41	38.5	54	60.5	64	3	4.5	0.8	1.5	0.54	1.1	0.6							
31,750	73,025	29,370	81.5	95	10.4	7500	10000	0.62	*HM88542/2/510/2/QCL7C	HM88500	31,750	56.9	27,783	23,020	1.3	3.3	23	42	38	55	62	69	3	6	1.3	3	0.54	1.1	0.6							
1,2500	2,8750	1,1563	70.4	95	10.4	6700	10000	0.62	HM88542/510/Q	HM88500	1,2500	56.9	1,0938	0,9063	0.05	0.13	23	42	38	55	62	69	3	6	1.3	3	0.54	1.1	0.6							
31,750	73,025	29,370	70.4	95	10.4	6700	10000	0.62	HM88542/510/Q	HM88500	31,750	56.9	27,783	23,020	1.3	3.3	23	42	38	55	62	69	3	6	1.3	3	0.54	1.1	0.6							
1,2500	2,4409	0,7500	56	57	6.2	9000	12000	0.24	*15123/15245/Q	15000	1,2500	45.8	0,7500	0,5625	0.16	0.05	13	38	44	54	55	58	4	3.5	3	1.3	0.35	1.7	0.9							
31,750	62	19,050	56	57	6.2	9000	12000	0.24	*15123/15245/Q	15000	31,750	45.8	19,050	14,288	4	1.3	13	38	44	54	55	58	4	3.5	3	1.3	0.35	1.7	0.9							
31,750	61,912	19,050	56	57	6.2	9000	12000	0.24	*15123/15243/Q	15000	31,750	45.8	19,050	14,288	4	2	13	38	44	54	55	58	4	3.5	3	2	0.35	1.7	0.9							